



ATR200 tag reader

- > Wiegand compatible
- > RS232 and RS485 compatible
- > Multiple power source option
- > Available as a single or dual reader
- > Variable receive range



DESCRIPTION

The ATR200 is an Active Tag Reader that has 3 interface systems, multiple power option, 2 firmware versions and is available as either a single or dual receiver.

The three data interfaces are RS232, RS485 and Wiegand, where the RS232 allows a single reader to be plugged into a COM port of a computer or similar device. The 2 wire RS485 allows multiple tag readers to be interfaced to a single com port on a computer or similar device, whilst the Weigand allows the ATR200 to be used with existing, Wiegand compatible access control systems.

The two Firmware versions consist of the polled software allowing computers to talk to the ATR200's one-by-one, which provides the benefit that multiple ATR200's can be attached to one com port.

The Minecom ATR200 is purely a receiver and the receive distance of the unit is reliant upon the output power of the tags being used within the system. High power tags with good external antennas such as the Vehicle Tag can have a potential range of up to 250 metres. Personal tags are available, however have a limited range.

LOCATIONS ACROSS AUSTRALIA,
NEW ZEALAND & MALAYSIA

For all your mining communications call

+61 3 9896 3000

or email sales@minecom.com

TR Corporation Pty Ltd

6 Joseph Street (PO Box 1185)

Blackburn North VIC 3130

AUSTRALIA

ABN: 99 005 499 721

www.minecom.com